

imageRUNNER 1700 Series Side-by-side

1750/1740/1730

Output Speed (LTR)

1750 52 ppm

1740 42 ppm

1730 32 ppm



Scan Speed 52/52/32 ipm

(LTR,300 dpi) (1750/1740/1730)

Basic Specifications

5.7" BW
QVGA LCD

512MB
Memory

550 x1
Cassette

Energy
Star

120V
9.3/6.9/6.2A

10/100
Ethernet

USB 2.0

Standard Functions

Copy

UFR II LT

Color
Scan

Color
Send

PDF
Compact

Scan to
USB

LDAP
Address Bk

AuSend

IEEE
802.1X

1750iF/1740iF/1730iF

Output Speed (LTR)

1750iF 52 ppm

1740iF 42 ppm

1730iF 32 ppm



Scan Speed 52/52/32 ipm

(LTR,300 dpi) (1750iF/1740iF/1730iF)

Basic Specifications

5.7" BW
QVGA LCD

512MB
Memory

550 x1
Cassette

Energy
Star

120V
9.3/6.9/6.2A

10/100
Ethernet

USB 2.0

Standard Functions

Copy

UFR II LT

Color
Scan

Color
Send

PDF
Compact

Scan to
USB

LDAP
Address Bk

AuSend

IEEE
802.1X

Standard for iF models

PCL

PS 3
Emulated

Searchable
PDF

FAX